

MICROCAT[®]-DF213

Biocompatible Defoamer for Wastewater Plants

Description

MICROCAT-DF213 Defoamer is a synthetic biocompatible organo-silicone liquid for controlling chemically generated foams (e.g, surfactants) in wastewater plants. It is formulated for aeration tanks and sludge digesters to suppress foam without inhibition of the biomass and other negative side effects associated with conventional defoamers. **MICROCAT – DF213** does not contain mineral oil, nitrogen or phosphorus compounds. As such it is compatible with the use of MICROCAT microbial – enzyme formulations.

Applications

At times anaerobic and aerobic microbial metabolism can result in persistent foams resulting from the presence of both natural and synthetic surface active agents such as detergents, cleaning compounds, soaps, etc.

Some foams can at times attain a “structural” character. **MICROCAT-DF213** can help, especially when used in conjunction with other **MICROCAT** products for controlling incoming greases and fats in the collection system. Such compounds and their metabolites tend to be surface active in their own right.



Before



After

Significant cost reductions versus conventional chemical foam treatments are available by combining **MICROCAT – DF213** with other **MICROCAT** formulations to create a “green” solution to a foaming problem.

Product Characteristics

Appearance	White, opaque viscous liquid
Contents	Synthetic, 100% active non-settleable organics
Shelf Life	One Year; Store above 50° F to avoid freezing.
Packaging	5/55 gallon (18.9 / 208.2 L) plastic drums, 275 gallon (1.04 m3) totes

Application Programs

In general, **MICROCAT-DF213** is metered continuously into the foam source. For anaerobic sludge digestion systems, add the product into the heat exchange loop. For aerobic sludge digestion systems add the product to the liquid surface. Add **MICROCAT – DF213** at a rate of 3 to 6 gallons per million gallons of digester volume. For “standing” foams of considerable depth increase the dose initially until the foam layer subsides and then reduce the application rate.

For aerobic wastewater systems add 3-15 ppm based on the forward flow rate. Add to the influent before the splitter box or to the sludge recycle line. If the foam blanket is greater than 3-4 inches, increase the application rate up to as high as 60 ppm until the layer subsides. Dosages as low as 0.5 – 5.0 ppm may control foam after initial foam collapse. Lower dosage slowly to obtain minimum required for control. The product can also be added batch-wise. Your Monera Technologies Corporation Technical Representative will provide you with a custom-tailored application program to fit your specific needs.

Application Equipment

Monera Technologies Corporation supplies cost-effective, metering equipment specially designed to ensure the efficacy of your foam control program. Contact your Monera Technologies Corporation Technical Representative for a complete site survey and detailed equipment recommendations.

Storage and Handling

Storage	55° - 120° F (13° - 49° C). Store indoors at room temperature.
Handling	No special handling required. Dispose of in accord with all local, state and federal requirements. If accidental skin contact occurs wash affected area with soap and water. Do not ingest. Non-toxic, non-pathogenic, harmless to aquatic life.

MICROCAT® is a registered trademark of Monera Technologies Corporation

The information contained in this data sheet is a guide to the use of **MICROCAT** products and is based on test and information believed to be reliable. Product content and specifications are subject to change without notice. All information is given to and accepted by user at user's risk and confirmation of its validity and suitability to particular cases should be obtained independently. Monera Technologies Corporation makes no guarantee of results and assumes no obligation or liability in connection with the information contained herein. Monera Technologies Corporation does not warrant against infringement of, and this data sheet is not to be construed as a license to operate under, any patents.