

MICROCAT[®]-ANSRL

Odor Control /Sludge Reduction Bioformula For Sludge Processing and Dewatering



Description

MICROCAT-ANSRL is a liquid blend of preselected, adapted microorganisms for use under microaerophilic, anoxic or anaerobic conditions. It is formulated for use in sludge drying beds and compost piles to suppress hydrogen sulfide odors and enhance biosolids biodegradation and contaminant removal where oxygen is of limited availability.

Applications

ODOR CONTROL

Anaerobic microbial metabolism frequently results in odors caused by sulfur-bearing compounds. Such odors arise in sludge handling and drying, composting and in wastewater treatment. **MICROCAT-ANSRL** can help. Its specialized microbes can convert sulfides under anaerobic or anoxic conditions to elemental sulfur, which is occluded by the cells thus suppressing odors. **MICROCAT-ANSRL** is particularly well suited to applications in sludge processing, handling and drying systems. Such systems are commonly found in wastewater processing facilities particularly activated sludge and related biosystems.

BIODEGRADATION

The release of waste biosolids into the environment creates odor and contamination problems. **MICROCAT-ANSRL** supplies an inoculum of preselected organisms for improving biodegradation of waste biosolids under non-ideal conditions. The biological treatment of wastewaters is always accompanied by the production of insoluble biosolids. The amount of these solids to be ultimately discarded can be reduced by the regular use of **MICROCAT-ANSRL** either in the system that produces them or in the downstream sludge processing, dewatering and drying systems.

Product Characteristics

Appearance	Light reddish brown, translucent, non-viscous liquid
Contents	Specialized, preselected, phototrophic and facultative anaerobes
Shelf Life	1.5 years when stored properly; Use activator
Packaging	Five / Fifty-five gallon (18.9 / 208.2 L) shielded plastic drums

Application Programs

In general, **MICROCAT-ANSRL** is applied (or metered) into the sludge on a preventive maintenance basis. Your Monera Technologies Corporation Technical Representative will provide you with a custom-tailored application program to fit your specific needs.

Optimal Application Conditions

For best results, apply this product under the following conditions:

Condition	Range	Optimum
Dissolved Oxygen, ppm	0 - 0.5	0.5
pH	6 - 9	7
Temperature, ° C	10 - 40	35
Toxic Heavy Metals, ppm	Trace	None

If your system is operating outside these ranges, contact your Monera Technologies Corporation Technical Representative for a complete system survey and recommendations.

Storage and Handling

06222020ANSRL

Storage	55° - 120° F (13° - 49° C). Store indoors at room temperature. DO NOT FREEZE. DO NOT STORE IN DIRECT SUNLIGHT.
Handling	CAUTION: If accidental skin contact occurs wash affected area with soap and water. Do not ingest. Non-toxic, non-pathogenic, harmless to aquatic life.

06222020ANSRL

MICROCAT® is a registered trademark of Bioscience, Inc. for use by Monera Technologies Corporation

The information contained in this data sheet is a guide to the use of MICROCAT products and is based on test and information believed to be reliable. Product content and specifications are subject to change without notice. All information is given to and accepted by user at user's risk and confirmation of its validity and suitability to particular cases should be obtained independently. Monera Technologies Corporation makes no guarantee of results and assumes no obligation or liability in connection with the information contained herein. Monera Technologies Corporation does not warrant against infringement of, and this data sheet is not to be construed as a license to operate under, any patents.

2201 Hangar Place, Suite 200 • Allentown, PA 18109 • (484) 245-5232 • Fax (484) 245-5236
Email: monera@moneratec.com Website: www.moneratec.com